

### Technical Data


Rated Voltage:415V

Current Rating:63A

Busbar Cross Section:16mm<sup>2</sup>Cu

Standard Length:1m

### Catalog NO.



For single pole device







Diagram	Type	Designation	Code
For single pole device	Pin Busbar	32A SP	1410321
	Pin Busbar	63A SP	1410631
	Pin Busbar	80A SP	1410801
	Pin Busbar	100A SP	1411001
	Fork Busbar	32A SP	1420321
	Fork Busbar	63A SP	1420631
	Fork Busbar	80A SP	1420801
	Fork Busbar	100A SP	1421001




For 2-pole device




For 2-pole device	Pin Busbar	32A DP	1410322
	Pin Busbar	63A DP	1410632
	Pin Busbar	80A DP	1410802
	Pin Busbar	100A DP	1411002
	Fork Busbar	32A DP	1420322
	Fork Busbar	63A DP	1420632
	Fork Busbar	80A DP	1420802
	Fork Busbar	100A DP	1421002




For 3-pole device



For 3-pole device	Pin Busbar	32A TP	1410323
	Pin Busbar	63A TP	1410633
	Pin Busbar	80A TP	1410803
	Pin Busbar	100A TP	1411003
	Fork Busbar	32A TP	1420323
	Fork Busbar	63A TP	1420633
	Fork Busbar	80A TP	1420803
	Fork Busbar	100A TP	1421003




For 4-pole device



For 4-pole device	Pin Busbar	32A FP	1410324
	Pin Busbar	63A FP	1410634
	Pin Busbar	80A FP	1410804
	Pin Busbar	100A FP	1411004
	Fork Busbar	32A FP	1420324
	Fork Busbar	63A FP	1420634
	Fork Busbar	80A FP	1420804
	Fork Busbar	100A FP	1421004



For 1P+N device (MCB AUB1N)



For 1P+N device (MCB AUB1N)	Pin Busbar	32A 1P+N	1410325
-----------------------------	------------	----------	---------